

HYDRO'ORP/A range

For private swimming pools

Oxidant Measure and Dosing

HYDRO range: ORP/A

In addition to the HYDRO range, SYCLOPE offers the HYDRO ORP/A.
This new equipment provides an oxidant measurement by the ORP* method with a 240 VAC, 2A power supply for direct control of a dosing system: dosing pump, valve...

HYDX524

Complete controller + sensors



SIGNIFICANT ADVANTAGES: *Performance, Efficiency & Safety*

- ▶ Automatic controller with dosing power adjustment or TOR** with hysteresis
- ▶ Sensor without any particular constraint of mounting
- ▶ Complete accessories kit (injection pipes, support collar...)
- ▶ Control of all type of dosing
- ▶ Can be mounted on panel with HYDRO'pH for chlorine or bromine control
- ▶ 2A circuit breaker integrated

The HYDRO range can be customized:

- logo and front face of your company
- specific features to be defined with our R&D department

ORP* : oxidation power by chlorine, bromine or ozone
TOR** : All or Nothing control

For other application, please contact us.



SYCLOPE
Electronique

Rue du Bruscos - 64230 SAUVAGNON - France
Tél.: +33(0)5 59 33 70 36 / Fax : +33(0)5 59 33 70 37
syclope@syclope.fr / www.syclope.fr

Stamp retailer